

8 / 16 CWA

Wallmount alarm unit



| | | |
|------------------------|--|---|
| Part # | 12830 | 12849 |
| Model | 8CWA | 16 CWA |
| Suitable for | 8 pcs. gas detectors | 16 pcs. gas detectors |
| Input terminal | 8 x 4-20mA signal | 16 x 4 - 20 mA |
| | SIMS NX RS-485, Profibus or MODBUS signal | |
| Output relays | 8CWA 24 free matrix programmable 4 assigned for: Warning; A1; A2 & Error | 16 CWA 16 free matrix programmable 4 assigned for: Warning; A1; A2 & Error |
| Output terminals | Potential free for output relays including W; A1; A2 & Error. RS-485 (SIMS-NX Protocol) Profibus or MODBUS | |
| Buzzer | Optional Integrated | |
| Operating temperature | 5° - 40° C | |
| Operating humidity | 20 % - 80% RH (non condensing) | |
| Dimensions (approx.) | 300 (H) x 300 (W)x 190 (D) mm | |
| Weight (approx.) | 7.1 kg | |
| Power requirements | 230 VAC, Max. 60 Watt 1) | |
| Classification housing | IP-65 | |
| Country of origin | Netherlands | |

1) an additional power supply (part # 12966) is required in case 3 or more suction type units are connected

